

## Transform your space.

Wallworks Aspect acoustical panels provide outstanding sound absorption and a clean appearance with minimal installation effort.



## Description

Aspect acoustical panels are the premier choice for applications that require high performance acoustic panels. Easy to install and available in a wide range of colors, sizes and shapes. Faced with any acoustic fabric, or a glass wool tissue that can be colored to match any standard RAL color.

## Core Material

High density rigid acoustical fibreglass containing 46% post-consumer content.

## Fire Performance

CAN/ULC S102: Flame Spread Index 25 or less. Smoke Developed Index 50 or less.

ATSM E84: Flame Spread Index 20 or less. Smoke Developed Index 0.

## Thickness

Available between 12mm and 40mm.

## Panel Sizes

Standard 24"x24", 24"x48"  
Custom sizes and shapes available

## Mounting Options

Walls: Impaling Clip or Adhesive direct to wall  
Suspended Ceilings: Standard hanger wire

## Acoustical Performance

|      | 125 Hz | 250 Hz | 500 Hz | 1000 Hz | 2000 Hz | 4000 Hz | NRC  |
|------|--------|--------|--------|---------|---------|---------|------|
| 25mm | 0.13   | 0.45   | 0.93   | 1.01    | 1.00    | 1.03    | 0.90 |



Contact our sales team for detailed options and pricing:

Toll Free: 877.829.2550

[sales@wallworks.com](mailto:sales@wallworks.com)

Fax: 855.896.8893

[www.wallworks.com](http://www.wallworks.com)

Find us on:

